







DYASfilm

Water-resistant DYAS FILM is made of many plies of rotary-cut beech veneers glued together with a phenol-formaldehyde adhesive. The grains of adjoining layers are at right angles to each other. The surface is covered on both sides by a phenolic film and its edges are painted with a protective water-resistand coating.

> Certificate ISO9001 Certificate PEFC

www.dyas.eu





DYAS Film

Is a health harmless plywood complying with the E-1 Class of formaldehyde escape according to ČSN EN 717-1.

Application:

DYAS Film is mainly used in the building industry for the production of building elements. It is also widely used for the production of containers, railway carriages, poster surfaces, agricultural constructions, for shuttering and as a flooring in the trucks and trailers.

Thickness:

9, 10, 12, 15, 18, 21, 25, 30, 35 mm (special thicknesses on customers´ request)

Gluing:

Class of gluing 3 (AW 100) - ČSN EN 314-2 – can be used in unprotected exterior areas according to ČSN EN 636-3

Dimensions:

1 250 x 2 500 mm 1 500 x 2 500 mm (cut-to sizes on customers´ request)

Quality:

As per PN 8/DY/97 – water resistant plywood with phenolic film finish

Type:

antislip/ smooth

Moisture:

6% to 12% (at the time of delivery)

Surface:

Surface is covered with a phenolic film of cca 150g/m²

Thickness	Number of plies	Volume weight	Thickness tolerance	Bending strength (surface veneer grain orientation)	
		(kg/m³)	(mm)	podélný	příčný
9	5x/7x	780-810	+0,2/-0,5	60,0 N/mm²	30,0 N/mm²
10	7х				
12	7x/9x				
15	9x/11x		+0,2/-0,7		
18	11x/13x				
21	13x/15x		+0,3/-1,0		
25	15×				
27	15×		+0,3/-1,2		
30	17×				

DYAS.EU, a.s. Veselská 384 | 687 24 | Uherský Ostroh | CZ tel.: +420 572 412 207 | fax.: +420 572 412 213 e-mail: dyas@dyas.eu | www. dyas.eu

DYAS flm

QUALITY IN ALL LAYERS SINCE 1930