

Declaration of Performance (DoP)

No.: 15/2017

Name of product:	Frame – raw, gluing class 1
Product ID:	20 20 11 25
Product intended for:	internal use as non-structural components in dry conditions
Producer:	DYAS.EU, a.s. Dukelských hrdinů 3653/1 695 58 Hodonín, Czech Republic
Company registration Nr.:	271 176 51
Plant:	Veselská 384, 687 24 Uherský Ostroh, Czech Republic
Assessment method:	4
Testing laboratory:	Výzkumný a vývojový ústav dřevařský, Praha, s.p. Na Florenci 7-9 111 71 Praha 1

Notified body No.: 1393
Authorized person No.: 222

Carried out determination of formaldehyde emission by method of gas analysis according to EN 717-2.

Issued a test record, **the product meets the emission class E-1.**

DYAS.EU, a.s., Dukelských hrdinů 3653/1, 695 58 Hodonín,
Provozovna: Veselská 384, 687 24 Uherský Ostroh
IČO: 27117651, DIČ: CZ27117651, Fax: + 420 572 591 439, dyas@dyas.eu
Společnost je zapsaná v OR KS v Brně, oddíl B, vložka 4486, www.dyas.eu



Kvalita ve všech vrstvách - založeno 1930

www.dyas.eu

Product features :

No.	Basic characteristics	Feature	Harmonized norm
1	Bending strength – longwise (minimal guaranteed strength)	80,00 N / mm ²	EN 310
2	Gluing quality – EN 636 - 1	Gluing class – 1	EN 314 - 2
4	Formaldehyde release	E – 1	EN 717-2
5	Reaction to fire without air gap behind a wood-based board (thickness ≥ 9mm)	D-s2,d0 for floors Dfl – s1	EN 13986+A1
	Reaction to fire with closed or open air gap up to 22 mm (thickness ≥ 9 mm)	D-s2, d2	
	Reaction to fire with closed air gap behind the wood-based board (thickness ≥ 15mm)	D-s2,d0 for floors Dfl – s1	
	Reaction to fire with open air gap behind the wood-based board (thickness ≥ 18mm)	D-s2,d0 for floors Dfl – s1	
6	Water vapour permeability – diffusion resistance factor μ humid	90	EN 13986+A1
	Water vapour permeability – diffusion resistance factor μ dry	220	EN 13986+A1
7	Sound-transmission loss – applies to the frequency range from 1 kHz to 3 kHz (thickness 10 – 50mm)	From 25 to 35 dB	EN 13986+A1
8	Sound absorption factor – frequency range from 250 Hz to 500 Hz	0,1	EN 13986+A1
	Sound absorption factor – frequency range from 1 kHz to 2 kHz	0,3	EN 13986+A1
9	Thermal conductivity - λ	0,17 W/(m.K)	EN 13986+A1
10	Biological durability – class of danger	3	EN 335
11	Pentachlorophenol content- no substance containing pentachlorophenol was used in the manufacture	not determined	EN 13986+A1

Product features – Frame – raw, gluing class 1 is in compliance with the properties listed in the "Product features" table.

This declaration of performance is issued under the responsibility of DYAS.EU, a.s.

Signed on behalf of the producer and his name :



.....
Radek Nejeschleba
Managing Director

In Uherský Ostroh dated 6th October 2017

2/2

DYAS.EU, a.s., Dukelských hrdinů 3653/1, 695 58 Hodonín,
Provozovna: Veselská 384, 687 24 Uherský Ostroh
IČO: 27117651, DIČ: CZ27117651, Fax: + 420 572 591 439, dyas@dyas.eu
Společnost je zapsaná v OR KS v Brně, oddíl B, vložka 4486, www.dyas.eu

Kvalita ve všech vrstvách - založeno 1930

www.dyas.eu

